



The rigid stem configuration makes installation fast and easy.



The flexible configuration is designed for applications requiring further thermal isolation or where installation would be otherwise difficult or impractical.

Main features

The W0 Series is a melt pressure control system which comes complete with the following items:

- W3x-6-M-xxxx-1-4-D-000 (oil-filled melt pressure transducer)
- 2500-0-0-0-W-0-1 (pressure controller)
- C08WLS (25 foot 6-pin cable)
- SF18 (mounting bracket)

Controller:

- Economically priced
- Displays pressure in a 5-digit LED display
- Auto zero
- Auto span
- Auto calibration
- 4 alarms with adjustable setpoint
- Touch-type keypad
- Built-in strain gauge bridge excitation
- Filter for digit stabilization
- Coded access for user lockout

Transducer:

- Better than $\pm 0.50\%$ accuracy
- Fluid-filled system for temperature stability
- 80% output signal for easy calibration
- 17-7 PH stainless steel corrugated diaphragm with GTP coating
- Oil-fill is FDA approved — meets requirements CFR172.3620 and CFR172.878

The W0 Series is an excellent solution for those who wish to have the accuracy and stability of a transducer and digital controller at a great price.

TECHNICAL SPECIFICATIONS

See data sheets for W3 and 2500-0-0-0-W-0-1 for more information.

ACCESSORIES

Connectors

6-pin mating connector (IP65 protection degree)CON300

Extension cables

6-pin connector with 8m (25ft) cableC08WLS (standard)

6-pin connector with 15m (50ft) cableC15WLS *

6-pin connector with 25m (75ft) cableC25WLS *

6-pin connector with 30m (100ft) cableC30WLS *

* Consult factory for ordering and pricing

Accessories

Mounting bracketSF18

Dummy plug for 1/2-20UNFSC12

Drill kit for 1/2-20UNFKF12

Cleaning kit for 1/2-20UNFCT12

Cable Wiring Code

Function	Wire
Sig (+)	Red
Sig (-)	Black
Exc (+)	White
Exc (-)	Green
Cal (+)	Blue
Cal (-)	Brown

<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2" style="text-align: left;">SYSTEM</th> </tr> <tr> <td style="width: 80%;">Controller (2301)</td> <td style="width: 20%; text-align: center;">0</td> </tr> </table> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2" style="text-align: left;">VERSION</th> </tr> <tr> <td style="width: 80%;">Rigid Stem</td> <td style="width: 20%; text-align: center;">0</td> </tr> <tr> <td>Rigid Stem + Flex</td> <td style="text-align: center;">1</td> </tr> </table> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2" style="text-align: left;">CONNECTOR</th> </tr> <tr> <td style="width: 80%;">Standard</td> <td style="width: 20%;"></td> </tr> <tr> <td>6 pin</td> <td style="text-align: center;">6</td> </tr> </table> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2" style="text-align: left;">ACCURACY CLASS</th> </tr> <tr> <td style="width: 80%;">0.50% FSO</td> <td style="width: 20%; text-align: center;">M</td> </tr> </table> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="4" style="text-align: left;">RANGE</th> </tr> <tr> <th colspan="2" style="text-align: left;">bar</th> <th colspan="2" style="text-align: left;">psi</th> </tr> <tr> <td style="width: 15%;">35</td> <td style="width: 15%;">B35U</td> <td style="width: 15%;">500</td> <td style="width: 15%;">P05C</td> </tr> <tr> <td>70</td> <td>B07D</td> <td>1000</td> <td>P01M</td> </tr> <tr> <td>100</td> <td>B01C</td> <td>1500</td> <td>P15C</td> </tr> <tr> <td>200</td> <td>B02C</td> <td>3000</td> <td>P03M</td> </tr> <tr> <td>350</td> <td>B35D</td> <td>5000</td> <td>P05M</td> </tr> <tr> <td>500</td> <td>B05C</td> <td>7500</td> <td>P75C</td> </tr> <tr> <td>700</td> <td>B07C</td> <td>10000</td> <td>P10M</td> </tr> </table>	SYSTEM		Controller (2301)	0	VERSION		Rigid Stem	0	Rigid Stem + Flex	1	CONNECTOR		Standard		6 pin	6	ACCURACY CLASS		0.50% FSO	M	RANGE				bar		psi		35	B35U	500	P05C	70	B07D	1000	P01M	100	B01C	1500	P15C	200	B02C	3000	P03M	350	B35D	5000	P05M	500	B05C	7500	P75C	700	B07C	10000	P10M	W0 - M - 000 000 = standard version <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2" style="text-align: left;">FLEXIBLE LENGTH (mm, inches)</th> </tr> <tr> <td colspan="2">Standard (W00)</td> </tr> <tr> <td style="width: 10%; text-align: center;">0</td> <td>none</td> </tr> <tr> <td colspan="2">Standard (W01)</td> </tr> <tr> <td style="text-align: center;">D</td> <td>457 mm, 18"</td> </tr> </table> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2" style="text-align: left;">RIGID STEM LENGTH (mm, inches)</th> </tr> <tr> <td style="width: 10%; text-align: center;">4</td> <td>153 mm, 6"</td> </tr> <tr> <td style="text-align: center;">5</td> <td>318 mm, 12.5"</td> </tr> </table> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2" style="text-align: left;">THREAD</th> </tr> <tr> <td style="width: 10%; text-align: center;">1</td> <td>1/2-20 UNF</td> </tr> </table>	FLEXIBLE LENGTH (mm, inches)		Standard (W00)		0	none	Standard (W01)		D	457 mm, 18"	RIGID STEM LENGTH (mm, inches)		4	153 mm, 6"	5	318 mm, 12.5"	THREAD		1	1/2-20 UNF
SYSTEM																																																																													
Controller (2301)	0																																																																												
VERSION																																																																													
Rigid Stem	0																																																																												
Rigid Stem + Flex	1																																																																												
CONNECTOR																																																																													
Standard																																																																													
6 pin	6																																																																												
ACCURACY CLASS																																																																													
0.50% FSO	M																																																																												
RANGE																																																																													
bar		psi																																																																											
35	B35U	500	P05C																																																																										
70	B07D	1000	P01M																																																																										
100	B01C	1500	P15C																																																																										
200	B02C	3000	P03M																																																																										
350	B35D	5000	P05M																																																																										
500	B05C	7500	P75C																																																																										
700	B07C	10000	P10M																																																																										
FLEXIBLE LENGTH (mm, inches)																																																																													
Standard (W00)																																																																													
0	none																																																																												
Standard (W01)																																																																													
D	457 mm, 18"																																																																												
RIGID STEM LENGTH (mm, inches)																																																																													
4	153 mm, 6"																																																																												
5	318 mm, 12.5"																																																																												
THREAD																																																																													
1	1/2-20 UNF																																																																												

Examples

W01-6-M-B07C-1-4-D-000

Melt pressure control system with rigid stem and flex transducer, 6-pin connector/cable, 1/2-20 UNF thread, 700 bar full scale output, 0.50% accuracy class, 153 mm (6") rigid stem, 457 mm (18") flex

W00-6-M-P03M-1-4-0-000

Melt pressure control system with rigid stem transducer, 6-pin connector/cable, 1/2-20 UNF thread, 3000 psi full scale output, 0.50% accuracy class, 153 mm (6") rigid stem

GEFRAN reserves the right to make any kind of design or functional modification at any moment without prior notice.