

GEFRAN (OIL-FILLED)

1/8 DIN



The rigid stem configuration makes installation fast and easy.



The flexible configuration is designed for applications requiring further thermal isolation or where installation would be otherwise difficult or impractical.

Main features

The W7 Series is a melt pressure monitoring system which comes complete with the following items:

- W3x-6-M-xxxx-1-4-D-000 (oil-filled melt pressure transducer)
- 40B-96-5-10-RR-R0-3-0-1 (1/8 DIN pressure indicator)
- C08WLS (25 foot 6-pin cable)
- SF18 (mounting bracket)

Indicator:

- Economically priced
- Displays pressure in a 5-digit LED display
- Auto zero
- Auto span
- Auto calibration
- 2 alarms with adjustable setpoint
- Touch-type keypad
- Built-in strain gage bridge excitation
- Filter for digit stabilization
- Coded access for user lockout

Transducer:

- Better than $\pm 0.50\%$ accuracy
- Fluid-filled system for temperature stability
- 80% output signal for easy calibration
- 17-7 PH stainless steel corrugated diaphragm with GTP coating
- Oil-fill is FDA approved — meets requirements CFR172.3620 and CFR172.878

The W7 Series is an excellent solution for those who wish to have the accuracy and stability of a transducer and digital indicator at a great price.

TECHNICAL SPECIFICATIONS

See data sheets for W3 and

40B-96-5-10-RR-R0-3-0-1 for more information.

ACCESSORIES

Connectors

6-pin mating connector (IP65 protection degree)CON300

Extension cables

6-pin connector with 8m (25ft) cableC08WLS (standard)

6-pin connector with 15m (50ft) cableC15WLS *

6-pin connector with 25m (75ft) cableC25WLS *

6-pin connector with 30m (100ft) cableC30WLS *

* Consult factory for ordering and pricing

Accessories

Mounting bracketSF18

Dummy plug for 1/2-20UNFSC12

Drill kit for 1/2-20UNFKF12

Cleaning kit for 1/2-20UNFCT12

Cable Wiring Code

Function	Wire
Sig (+)	Red
Sig (-)	Black
Exc (+)	White
Exc (-)	Green
Cal	Blue
Cal	Brown

SYSTEM		7	W	M							000
1/8 DIN System		7									
VERSION											
Rigid Stem		0									
Rigid Stem + Flex		1									
CONNECTOR											
Standard											
6 pin		6									
ACCURACY CLASS											
0.50% FSO		M									
RANGE											
bar		psi									
35	B35U	500	P05C								
70	B07D	1000	P01M								
100	B01C	1500	P15C								
200	B02C	3000	P03M								
350	B35D	5000	P05M								
500	B05C	7500	P75C								
700	B07C	10000	P10M								
FLEXIBLE LENGTH (mm, inches)											
Standard (W70)											
0	none										
Standard (W71)											
D	457 mm, 18"										
RIGID STEM LENGTH (mm, inches)											
4	153 mm, 6"										
5	318 mm, 12.5"										
THREAD											
1	1/2-20 UNF										

Examples

W71-6-M-B07C-1-4-D-000

Melt pressure monitoring system (1/8 DIN) with oil-filled rigid stem and flex transducer, 6-pin connector/cable, 1/2-20 UNF thread, 700 bar full scale output, 0.50% accuracy class, 153 mm (6") rigid stem, 457 mm (18") flex

W70-6-M-P03M-1-4-0-000

Melt pressure monitoring system (1/8 DIN) with oil-filled rigid stem transducer, 6-pin connector/cable, 1/2-20 UNF thread, 3000 psi full scale output, 0.50% accuracy class, 153 mm (6") rigid stem

GEFRAN reserves the right to make any kind of design or functional modification at any moment without prior notice.